

Ideal for permanent installation into indoor sports or music venues, Fv series is an SMD fascia panel that features a special 'drink cap' to protect it from liquid ingress such as drinks spilt from above, meaning that accidents won't stop fans viewing pleasure.


Fv series offers 2,000 nits of brightness and can be used for a wide range of applications such as match relay, advertising banner panels or relaying important information. As with all Lighthouse products, its true color representation makes it the perfect choice for any situation where accurate representation of brand image is critical.

Fv

Permanent
Indoor
Top Access
SMD LED
Panel



Indoor Sports Arenas



Fv10 / Fv20

10x1	12.80m (41.90ft.) x 0.80m (2.62ft)
9x1	11.52m (37.71ft.) x 0.80m (2.62ft)
8x1	10.24m (33.52ft.) x 0.80m (2.62ft)
7x1	8.96m (29.33ft.) x 0.80m (2.62ft)
6x1	7.68m (25.14ft.) x 0.80m (2.62ft)
5x1	6.40m (20.95ft.) x 0.80m (2.62ft)
4x1	5.12m (16.76ft.) x 0.80m (2.62ft)
1x1	1.28m (4.19ft.) x 0.80m (2.62ft)







		Fv10	Fv16-TA	Fv20-TA
Visual Characteristics			2,000	
	nits		160 (+80 / -80)	
Brightness	deg.		140 (+70 / -70)	
Visual Viewing Angle - Horizontal	deg.		SMD 3-in-1	
Visual Viewing Angle - Vertical	R/G/B		15.875	20
Pixel Configuration	mm	10	16	
Pixel Pitch	bit		10	
Processing Depth				8:5
Modular Characteristics		8:5	4:3	1280 / 4.2
Aspect Ratio	/ Cb	1280 / 4.20	1016 / 3.33	800 /2.62
	mm / ft	800 / 2.62	762 / 2.5	
Panel Width	mm / ft		0.774 / 8.33	1.024 / 11
Panel Height	sq.m / sq.ft	1.024 / 11 .02	64 x 48	64 x 40
Panel Surface Area	wxh	128 x 80	UTA	
Pixel Resolution			IP40 / IP20	
Environmental	IP			
Ingress Protection (Front / Rear)	ir		≥100,000	
`	hrs			
Lifetime (50% brightness)	ov specifications without r	notice.		

^{*} Lighthouse reserves the right to change any specifications without notice.